

NSW MARITIME

Safety Equipment

Enclosed Waters				
All safety equipment must meet minimum standards, be in good working order and easily accessible.				
Equipment	Under 5 m	5-8 m	8-12m	12m & above
Lifejackets (Approved 1, 2 or 3)	1 per person			
Paddles or Oars/Rowlocks	Not required if 2 independent means of propulsion fitted		Not Required	
Bucket or Bailer with lanyard attached (Minimum capacity 2 litres)	1			
Bucket with lanyard attached (Minimum Capacity 9 litres)	1		2	
Bilge Pump(s) (Capacity)	Optional or One (45 litres/per min)		One (45 litres/per min)	One (65 litres/per min)
Fire Extinguisher(s) Where any fuel is carried except open vessels under 5m Where propulsion or cooking fuel is carried below deck	1 or 1	1 1	2 1	2 2
Waterproof Torch	One required if operating between sunset and sunrise			
Anchor, chain/line attached	1			2
Lifebuoy with 30m line	Not required on vessels less than 8m		Note: A vessel 8-12m long may carry a buoyant rescue quoit with 15m of line instead of the lifebuoy	1
Navigation Lights	Required by all vessels between sunset and sunrise and in restricted visibility			
Sound Signals	An efficient sound signal device			Whistle and bell